

1. Identification

Product identifier Single Stage Acrylic Urethane Paint Bright White

Other means of identification

Product code SPK9710

Recommended use Paint

Recommended restrictions No other uses are advised.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name SpeedoKote LLC.
Address 5701 N. Webster St.
Dayton, OH 45414
United States

Telephone TECH SUPPORT 937-280-0091
SALES 937-280-0091
PHONE 937-280-0091

Website www.speedokote.com

E-mail sales@speedokote.com

Contact person Safety Department

Emergency phone number EMERGENCY 24 Hrs. 800-424-9300 ChemTrec

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1B
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 3
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

Storage

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

27.99% of the mixture consists of component(s) of unknown acute oral toxicity. 61.01% of the mixture consists of component(s) of unknown acute dermal toxicity. % of the mixture consists of component(s) of unknown acute inhalation toxicity. 45.49% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 45.49% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
N-Butyl Acetate		123-86-4	20 - < 30
Titanium Dioxide		13463-67-7	20 - < 30
Methyl Acetate		79-20-9	5 - < 10
Methyl n-Amyl Ketone		110-43-0	5 - < 10
Aluminum Hydroxide		21645-51-2	1 - < 3
BENZENE, M-DIMETHYL-		108-38-3	1 - < 3
BENZENE, P-DIMETHYL-		106-42-3	1 - < 3
ETHYLBENZENE		100-41-4	1 - < 3
BENZENE, O-DIMETHYL		95-47-6	< 1
Petroleum Distillates, Hydrotreated Light		64742-47-8	< 1
Bis(1, 2, 2, 6, 6-Pentamethyl-4-piperidiny) Sebacate		41556-26-7	< 0.3
Xylene		1330-20-7	< 0.3

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Carbon dioxide (CO ₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
BENZENE, M-DIMETHYL- (CAS 108-38-3)	PEL	435 mg/m ³	
		100 ppm	
BENZENE, O-DIMETHYL (CAS 95-47-6)	PEL	435 mg/m ³	
		100 ppm	
BENZENE, P-DIMETHYL- (CAS 106-42-3)	PEL	435 mg/m ³	
		100 ppm	
ETHYLBENZENE (CAS 100-41-4)	PEL	435 mg/m ³	
		100 ppm	
Methyl Acetate (CAS 79-20-9)	PEL	610 mg/m ³	
		200 ppm	
Methyl n-Amyl Ketone (CAS 110-43-0)	PEL	465 mg/m ³	
		100 ppm	
N-Butyl Acetate (CAS 123-86-4)	PEL	710 mg/m ³	
		150 ppm	
Petroleum Distillates, Hydrotreated Light (CAS 64742-47-8)	PEL	400 mg/m ³	
		100 ppm	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m ³	Total dust.
Xylene (CAS 1330-20-7)	PEL	435 mg/m ³	

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
------------	------	-------	------

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
		100 ppm	
Aluminum Hydroxide (CAS 21645-51-2)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Aluminum Hydroxide (CAS 21645-51-2)	TWA	1 mg/m3	Respirable fraction.
BENZENE, M-DIMETHYL- (CAS 108-38-3)	STEL	150 ppm	
	TWA	100 ppm	
BENZENE, O-DIMETHYL (CAS 95-47-6)	STEL	150 ppm	
	TWA	100 ppm	
BENZENE, P-DIMETHYL- (CAS 106-42-3)	STEL	150 ppm	
	TWA	100 ppm	
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm	
Methyl Acetate (CAS 79-20-9)	STEL	250 ppm	
	TWA	200 ppm	
Methyl n-Amyl Ketone (CAS 110-43-0)	TWA	50 ppm	
N-Butyl Acetate (CAS 123-86-4)	STEL	150 ppm	
	TWA	50 ppm	
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
BENZENE, M-DIMETHYL- (CAS 108-38-3)	STEL	655 mg/m3
		150 ppm
	TWA	435 mg/m3
		100 ppm
BENZENE, O-DIMETHYL (CAS 95-47-6)	STEL	655 mg/m3
		150 ppm
	TWA	435 mg/m3
		100 ppm
BENZENE, P-DIMETHYL- (CAS 106-42-3)	STEL	655 mg/m3
		150 ppm
	TWA	435 mg/m3
		100 ppm
ETHYLBENZENE (CAS 100-41-4)	STEL	545 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Methyl Acetate (CAS 79-20-9)	TWA	125 ppm
		435 mg/m ³
	STEL	100 ppm
		760 mg/m ³
Methyl n-Amyl Ketone (CAS 110-43-0)	TWA	250 ppm
		610 mg/m ³
		200 ppm
N-Butyl Acetate (CAS 123-86-4)	STEL	465 mg/m ³
		100 ppm
	TWA	950 mg/m ³
		200 ppm
		710 mg/m ³
		150 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
BENZENE, M-DIMETHYL- (CAS 108-38-3)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
BENZENE, O-DIMETHYL (CAS 95-47-6)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
BENZENE, P-DIMETHYL- (CAS 106-42-3)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.



General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Material name: Single Stage Acrylic Urethane Paint Bright White

SPK9710 Version #: 01 Issue date: 06-30-2017

SDS US

6 / 13

Physical state	Liquid.
Form	Liquid.
Color	White
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-144.4 °F (-98 °C) estimated
Initial boiling point and boiling range	134.24 °F (56.8 °C) estimated
Flash point	14.0 °F (-10.0 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.1 % estimated
Flammability limit - upper (%)	16 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	1712.53 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	740 °F (393.33 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	1.39 g/cm ³ estimated
Explosive properties	Not explosive.
Flammability class	Flammable IB estimated
Oxidizing properties	Not oxidizing.
Percent volatile	38.19 % estimated
Specific gravity	1.39 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Nitrates.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Harmful if inhaled.

Components	Species	Test Results
BENZENE, M-DIMETHYL- (CAS 108-38-3)		
<u>Acute</u>		
Oral		
LD50	Rat	4300 mg/kg
BENZENE, O-DIMETHYL (CAS 95-47-6)		
<u>Acute</u>		
Oral		
LD50	Rat	4300 mg/kg
BENZENE, P-DIMETHYL- (CAS 106-42-3)		
<u>Acute</u>		
Oral		
LD50	Rat	3523 - 8600 mg/kg
ETHYLBENZENE (CAS 100-41-4)		
<u>Acute</u>		
Oral		
LD50	Rat	3500 mg/kg
Methyl n-Amyl Ketone (CAS 110-43-0)		
<u>Acute</u>		
Oral		
LD50	Rat	1.67 g/kg
Xylene (CAS 1330-20-7)		
<u>Acute</u>		
Oral		
LD50	Rat	3523 - 8600 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

BENZENE, M-DIMETHYL- (CAS 108-38-3)	3 Not classifiable as to carcinogenicity to humans.
BENZENE, O-DIMETHYL (CAS 95-47-6)	3 Not classifiable as to carcinogenicity to humans.
BENZENE, P-DIMETHYL- (CAS 106-42-3)	3 Not classifiable as to carcinogenicity to humans.
ETHYLBENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Titanium Dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
BENZENE, M-DIMETHYL- (CAS 108-38-3)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 2.81 - 5 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 8.4 mg/l, 96 hours
BENZENE, O-DIMETHYL (CAS 95-47-6)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 0.78 - 2.51 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 5.59 - 11.6 mg/l, 96 hours
BENZENE, P-DIMETHYL- (CAS 106-42-3)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 3.55 - 6.31 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 2.6 mg/l, 96 hours
ETHYLBENZENE (CAS 100-41-4)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 7.5 - 11 mg/l, 96 hours
Methyl Acetate (CAS 79-20-9)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 295 - 348 mg/l, 96 hours
Methyl n-Amyl Ketone (CAS 110-43-0)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 126 - 137 mg/l, 96 hours
N-Butyl Acetate (CAS 123-86-4)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 17 - 19 mg/l, 96 hours
Petroleum Distillates, Hydrotreated Light (CAS 64742-47-8)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 2.9 mg/l, 96 hours
Titanium Dioxide (CAS 13463-67-7)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) > 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus) > 1000 mg/l, 96 hours

Components	Species	Test Results
Xylene (CAS 1330-20-7)		
Aquatic		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)
		7.711 - 9.591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

BENZENE, M-DIMETHYL-	3.2
BENZENE, O-DIMETHYL	3.12
BENZENE, P-DIMETHYL-	3.15
ETHYLBENZENE	3.15
Methyl Acetate	0.18
Methyl n-Amyl Ketone	1.98
N-Butyl Acetate	1.78
Xylene	3.12 - 3.2

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

The following transportation information is provided based on the manufacturer's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

DOT

UN number	UN1993
UN proper shipping name	Flammable liquids, n.o.s. (Rapid Cure Clearcoat, Methyl n-Amyl Ketone)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB2, T7, TP1, TP8, TP28
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242

IATA

UN number	UN1993
UN proper shipping name	Flammable liquid, n.o.s. (Rapid Cure Clearcoat, Methyl n-Amyl Ketone)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3H

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1993

UN proper shipping name FLAMMABLE LIQUID, N.O.S. (Rapid Cure Clearcoat, Methyl n-Amyl Ketone)

Transport hazard class(es)

Class 3

Subsidiary risk -

Packing group II

Environmental hazards

Marine pollutant No.

EmS F-E, S-E

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BENZENE, M-DIMETHYL- (CAS 108-38-3)	Listed.
BENZENE, O-DIMETHYL (CAS 95-47-6)	Listed.
BENZENE, P-DIMETHYL- (CAS 106-42-3)	Listed.
ETHYLBENZENE (CAS 100-41-4)	Listed.
Methyl Acetate (CAS 79-20-9)	Listed.
N-Butyl Acetate (CAS 123-86-4)	Listed.
Xylene (CAS 1330-20-7)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
BENZENE, M-DIMETHYL-	108-38-3	1 - < 3
BENZENE, O-DIMETHYL	95-47-6	< 1
BENZENE, P-DIMETHYL-	106-42-3	1 - < 3
ETHYLBENZENE	100-41-4	1 - < 3

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

BENZENE, M-DIMETHYL- (CAS 108-38-3)
 BENZENE, O-DIMETHYL (CAS 95-47-6)
 BENZENE, P-DIMETHYL- (CAS 106-42-3)
 ETHYLBENZENE (CAS 100-41-4)
 Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Methyl Acetate (CAS 79-20-9) Low priority
 Methyl n-Amyl Ketone (CAS 110-43-0) Other Flavoring Substances with OSHA PEL's
 N-Butyl Acetate (CAS 123-86-4) Low priority

US state regulations**WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

ETHYLBENZENE (CAS 100-41-4) Listed: June 11, 2004
 Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

US - California Proposition 65 - CRT: Listed date/Developmental toxin

BENZENE, METHYL- (CAS 108-88-3) Listed: January 1, 1991

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

BENZENE, M-DIMETHYL- (CAS 108-38-3)
 BENZENE, O-DIMETHYL (CAS 95-47-6)
 BENZENE, P-DIMETHYL- (CAS 106-42-3)
 Bis(1, 2, 2, 6, 6-Pentamethyl-4-piperidiny)l Sebacate (CAS 41556-26-7)
 ETHYLBENZENE (CAS 100-41-4)
 Titanium Dioxide (CAS 13463-67-7)
 Xylene (CAS 1330-20-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	06-30-2017
Version #	01
Disclaimer	SpeedoKote LLC. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.